

Q #	Page	Question	Option A	Option B	Option C	Option D	Option E	Error
4.41	58	Which one of the following must be in place when providing shower facilities on a site?	Shower cubicles that can be locked and are sufficient in number for both men and women to use in a communal welfare area	Shower cubicles that can be used by men and women but separated by a partition within a communal welfare area	Shower cubicles that can be used by men and women within a separate lockable room accessible to only one person at a time	Shower cubicles that can be used by men and women at pre-booked time slots which can be used by only one person at a time		Printing error, this question has been withdrawn from use in the test.
9.22	117	Which one of the following tasks would not expose a worker to lead fumes?	Burning off old paint with a hot-air gun	Soldering heating pipes	Removing old loft insulation	Working inside tanks that contained petrol		Option A should say 'Burning off old paint with a low-heat hot air gun'. This question has been removed from use in the test.
15.12	187	A painter is working from the platform of a mobile access tower. To prevent the operative from disembarking the tower to replenish paint materials, they are being hoisted up the outside of the tower. Which one of the following could be an outcome if not controlled sufficiently?	It could create limited space on the working platform	It could cause the tower to sway from side to side	It could significantly damage the tower assembly components	If could impact stability and cause the tower to overturn		Option D should begin with 'It' not 'If'
18.04	231	You are about to start a demolition project, and you are looking to employ a suitably qualified supervisor. How would you know if they met the requirements of the National Demolition Training Group? They would hold...	a Black card and a National Vocational Qualification (NVQ) Level 6 or higher	a Green card and a National Vocational Qualification (NVQ) Level 3 or higher	a Grey card and a National Vocational Qualification (NVQ) Level 3 or higher	a Blue card and a National Vocational Qualification (NVQ) Level 2 or higher		Option B is being updated to: B* a Gold card and a National Vocational Qualification (NVQ) Level 4 or higher. This question has been removed from use in the test.
12.47	158	When using liquefied petroleum gas cylinders on site it is important to follow which three procedures?	Keep all types of gas cylinder together in one area	Turn off cylinder valves before connecting any equipment	Check cylinders and associated equipment before use	Ensure that all cylinders are used horizontally to aid release of gas	Maximise the amount of gas cylinders on site at one time	Option E is incorrect due to a printing error, it should say 'minimise' not 'maximise'. This question has been removed from use in the test.
14.51	181	Which one of the following should be considered at a project's planning stage to reduce the risk to pedestrians and drivers from site traffic entering or exiting?	Provide trained marshals or signallers to control site vehicle movements	Control material stocks to ensure you have the right levels at the right time	Implement diversions for pedestrians away from site vehicle traffic routes	Regular meetings to inform the community of site traffic arrangements		This question has been removed from use in the test, as both 'divert site traffic away from pedestrianised areas' and 'use a banksman to direct vehicles' are quoted in the reference guidance (HSG151).

12.42	156	What does this warning label mean?	Explosive environment	Explosive atmosphere	Explosive substance	Explosive warning		This question has been removed from use in the test due to a printing error inserting the incorrect signage. The correct answer is option C.
18.16	234	What is the area called that receives materials from soft stripping or demolition operations?	The dumping zone	The landing zone	The placing zone	The waste zone		This question has been removed from use in the test. Following review with a member of the Demolition Federation, option B will be updated to 'drop zone'.
18.31	238	The height of a wall or building to be demolished should not normally be greater than the maximum reach of the machine being used to carry out the work. Is this correct?	No - the machine operator takes into account the height of the structure being demolished and the buildup of debris	Yes - this ensures that a safe distance is being maintained between the machine and the structure being demolished	No - the machine operator can construct a ramp, using rubble from previous demolition for the machine to sit on to increase the reach	Yes - this ensures that the machine operator is able to clearly see all elevations of the structure being demolished		This question has been removed from the test. Options B and C could be correct.
12.38	155	Which two of the following would not normally be included in a hot works permit?	Proposed start time and duration of the hot works	Instructions for checking for combustible materials in adjacent locations	Description and location of where the work will be completed	Information about the porosity content of materials being worked on	Identification and list of the people carrying out the works	This question has been removed from the test as option E would be included in the hot works permit.